

DATASHEET

ACTSAFE ICX POWER ASCENDER



GENERAL

Art.Nr:	POA-030-1-EU
GTIN:	4030281309840
Customs tariff number:	84253100

Net weight:	12.50 kg
Gross weight:	12.50 kg

DATASHEET

ACTSAFE ICX POWER ASCENDER

The ultralight, compact entry-level ActSafe ICX power ascender has been developed for a safe and efficient transport of persons in hard-to-reach areas. Paired with a rope, the ActSafe ICX forms an incredibly flexible system for the straightforward and cost-efficient cleaning and maintenance of complex structures. Its intuitive operation is effortlessly managed with a thumb wheel, enabling precise work. Equipped with a high-performance "Husqvarna" BLi200 battery, the hoist achieves an ascent speed of 24 m/min. The maximum battery range is 230 m with a 100 kg load and at a temperature of 20°C. Thanks to its IP55 rating, the ActSafe ICX can be used in all weather conditions. Rope loading is straightforward, streamlining your workflow and saving valuable time. Additionally, the control of the ActSafe ICX can be taken over by a second person on the ground using a remote control. This allows for the automatic ascent or descent of the individual operating the device, in case they are unable to do so themselves. Operating and utilizing the ActSafe ICX is quickly and easily learned through user training.

FEATURES

Colour:	Orange
Number of Rechargeable Batteries:	1
Battery range at 20° C & 100 kg load:	230 m
Energy source:	Removeable Battery
Underwater operations:	No
Water dust resistance:	IP 55
Charging time:	80 minutes
Minimum compatible rope diameter:	11.00 mm
Maximum compatible rope diameter:	11.00 mm
Minimum descent speed:	1 m/min
Maximum descent speed:	24 m/min
Min. ascent rate:	1 m/min
Max. ascent rate:	24 m/min
Minimum temperature:	-10 °C
Maximum temperature:	40 °C
Emergency descent function:	Yes
Emergency stop function:	Yes
Remote control range:	50 m
Working Load Limit:	185 kg

DATASHEET

ACTSAFE ICX POWER ASCENDER

MATERIAL

Material:	Steel, Aluminium, Nylon
-----------	----------------------------
